# STEAMIST®

Steam Generator
Features

Limited lifetime warranty - 2-year in home labor warranty where available

Generator typically can be installed up to 25 ft. from the bathing area

Selectable "Instamist"

Proportional Steam

"Gangable" up to (4) generator

Diagnostic LED Displays


Stainless Steel Construction

Solid-State Circuitry

#### Codes/Standards

UL 499

UL/CUL Listed



Steam Generator Specification Chart						
Model Number	Product Number	KW Rating	* Max. Cu. Ft. Range	Volts/Phase/ Max. Amps	Line Fuse	Dimensions L x W x H
TSG-7	7520 7521 7522 7523	7.5	250	240/1/31 208/1/36 240/3/18 208/3/21	40 50 30 30	15" x 6" x 15.5"
TSG-10	1020 1021 1022 1023	10	450	240/1/42 208/1/48 240/3/24 208/3/28	50 60 30 40	15" x 6" x 15.5"

<sup>\*</sup> Refer to sizing guidelines to accurately determine the proper size generator for the installation.

90°C copper wire is required for generator connection. Installation shall be in accordance with NEC and local electrical codes.

### Required Equipment

TSC Model Control

# Required Electrical Service

Dedicated circuit required: See Specification Chart for proper electrical requirements

## **Product Information**

Water Supply - %" Compression Fitting, 120 PSI Max Steam Line - ¾" Brass BPT male thread Pressure Relief Valve - ¾" NPT female thread Drain Line - Capped ½" Brass NPT male thread

#### Generator

Weight - 30 lbs.

#### Installation Notes

Steam Generators can be typically mounted within 25 ft. of the bathing area.

Steam Generators should be accessible for service.


Do NOT install near flammable material such as paints, thinners, gasoline, etc.

Steam generators must NOT be installed outdoors, in moist, humid areas, in areas prone to freezing, or extreme heat such as an unventilated attic. To do so will void the warranty.

Steamhead to be mounted 18" above floor or 6" above rim of tub and as far from the seating area as possible.

# Rough-in Notes

Access: 21" L x 20" W x 22" H (28" L with Auto Drain)



STEMMIST® East Coast Office: 25 E. Union Ave., East Rutherford, NJ 07073 • Tel: 800-577-6478 • Fax: 201-933-0746

West Coast Office: Tel: 800-355-6478 • Fax: 661-940-1617