

## Residential Upright Electric Water Heater




Photo is of  
RE250T6

### The Upright Electric Models Feature:

- **Fully Automatic Thermostat Controls**—Fast acting surface-mount thermostat with high limit energy cut-off (manual reset) for safety.
- **Direct Heat Transfer with Immersed Elements**—Transfers heat directly and efficiently to the water. Screw-in style.
- **Factory-Installed Hydrojet® Total Performance System**—Sediment reducing device that also increases first hour rating of hot water while minimizing temperature build-up in tank.
- **Vitraglas® Lining**—An exclusively engineered enamel formula that provides superior tank protection from the highly corrosive effects of hot water. This formula (Vitraglas®) is fused to the steel surface by firing at a temperature of over 1600°F (871°C).
- **Insulation System**—Non-CFC foam covers the sides and top of the tank, reducing heat loss. This results in less energy consumption, improved efficiencies, and jacket rigidity.
- **Water Connections**— 3/4" (19mm) NPT factory-installed true dielectric fittings extend water heater life and simplify water line connections.
- **Factory-Installed Heat Traps**—Design incorporates a flexible disk that reduces heat loss in piping and eliminates the potential for noise generation.
- **Protective Magnesium Anode Rod**—Provides added protection against corrosion for long-term, trouble-free service.
- **Simultaneous and Non-Simultaneous Operation Available**— Simultaneous operation indicates when both elements (if equipped) are being heated at the same time. Non-Simultaneous operation indicates when one element is being heated at a time.
- **Voltages Available**—120V, 208V, 240V, 277V, 480V.
- **Single Phase or Three Phase Operation Available**—120V & 277V may only be wired for single phase operation.
- **T&P Relief Valve**—Installed.
- **Design evaluated by ETL in accordance with Part 280.707(d) of HUD Mobile Home Construction and Safety Standards for Energy Efficiency.**

### FEATURING:



### 6 or 10-Year Limited Tank Warranties / 6 or 10-Year Limited Warranty on Component Parts.

For more information on warranty, please visit [www.bradfordwhite.com](http://www.bradfordwhite.com)  
For products installed in USA, Canada, and Puerto Rico. Some states do not allow limitations on warranties. See complete copy of the warranty included with the heater.

# Residential Upright Electric Water Heater

## Upright Models

Model Number	Capacity		Standby Loss (Watts)	First Hour Rating (Gal.)	Recovery 90°F Rise*		A Floor to Heater Top in.	B Jacket Dia. in.	C Floor to Water Conn. in.	D C/L of Water Conn. in.	E Floor to T&P Conn. in.	G Water Conn. NPT in.	Approx. Shipping Weight lbs.
	U.S. Gal.	Imp. Gal.			U.S. GPH	Imp. GPH							
RE230S6 $\mathbf{x}$	27	22	55	N/A	21	18	47	18	47 <sup>3/4</sup>	8	47 <sup>3/4</sup>	3/4	90
RE330S6	27	22	45	47	21	18	46 <sup>11/16</sup>	20	48 <sup>15/16</sup>	8	48 <sup>15/16</sup>	3/4	100
RE240S6 $\mathbf{x}$	38	32	63	55	21	18	47 <sup>3/16</sup>	20	49 <sup>7/16</sup>	8	49 <sup>7/16</sup>	3/4	123
RE340S6	38	32	53	55	21	18	47 <sup>3/16</sup>	22	49 <sup>7/16</sup>	8	49 <sup>7/16</sup>	3/4	114
RE340T6	37	31	52	56	21	18	60 <sup>3/16</sup>	20	62 <sup>7/16</sup>	8	62 <sup>7/16</sup>	3/4	125
RE250S6 $\mathbf{x}\mathbf{v}$	47	39	70	58	21	18	47 <sup>3/16</sup>	22	49 <sup>7/16</sup>	8	49 <sup>7/16</sup>	3/4	143
RE250T6 $\mathbf{x}\mathbf{v}$	47	39	63	64	21	18	59	20	60 <sup>1/4</sup>	8	60 <sup>1/4</sup>	3/4	130
RE350S6	47	39	59	67	21	18	47 <sup>3/16</sup>	24	49 <sup>7/16</sup>	8	49 <sup>7/16</sup>	3/4	144
RE265T6 $\mathbf{x}\mathbf{v}$	61	51	81	N/A	21	18	59 <sup>1/4</sup>	22	60 <sup>1/4</sup>	8	60 <sup>1/4</sup>	3/4	156
RE280T6	76	63	97	N/A	21	18	59 <sup>1/4</sup>	24	60 <sup>1/4</sup>	8	60 <sup>1/4</sup>	3/4	183

Model Number	Capacity		Standby Loss (Watts)	First Hour Rating (Litres)	Recovery 50°C Rise*		A Floor to Heater Top mm.	B Jacket Dia. mm.	C Floor to Water Conn. mm.	D C/L of Water Conn. mm.	E Floor to T&P Conn. mm.	G Water Conn. NPT mm.	Approx. Shipping Weight kg.
	Litres				Litres/Hour								
RE230S6 $\mathbf{x}$	102		55	N/A	80		1194	457	1213	203	1213	19	41
RE330S6	102		45	178	79		1186	508	1243	203	1243	19	45
RE240S6 $\mathbf{x}$	140		63	208	80		1199	508	1256	203	1256	19	56
RE340S6	140		53	205	79		1199	559	1256	203	1256	19	52
RE340T6	140		52	212	79		1529	508	1586	203	1586	19	57
RE250S6 $\mathbf{x}\mathbf{v}$	178		70	220	80		1199	559	1256	203	1256	19	65
RE250T6 $\mathbf{x}\mathbf{v}$	178		63	242	79		1499	508	1530	203	1530	19	59
RE350S6	178		59	254	79		1199	610	1256	203	1256	19	65
RE265T6 $\mathbf{x}\mathbf{v}$	231		81	N/A	80		1505	559	1530	203	1530	19	71
RE280T6	288		97	N/A	80		1505	610	1530	203	1530	19	83

265-52904-00- Bottom inlet kit must be installed with model to meet British Columbia or Ontario efficiency requirements.

Includes combination drain valve/cold water inlet and pipe cap for top water inlet.

- $\mathbf{v}$  Bottom inlet kit required to meet Ontario efficiency requirements.
- $\mathbf{x}$  Bottom inlet kit required to meet British Columbia efficiency requirements.

Standby loss (Watts) is based on top inlet location.



\* Based on 4500W/4500W, Non-Simultaneous operation.

For 10 year models, change suffix "6" to "10"

Wattage Limitations for Simultaneous Operation	Voltage					Wattage Limitations for Non-Simultaneous Operation	Voltage				
	120V	208V	240V	277V	480V		120V	208V	240V	277V	480V
1500W / 1500W	yes	yes	yes	yes	yes	1500W / 1500W	yes	yes	yes	yes	yes
2000W / 2000W	no	yes	yes	yes	yes	2000W / 2000W	yes	yes	yes	yes	yes
2500W / 2500W	no	yes	yes	yes	yes	2500W / 2500W	yes	yes	yes	yes	yes
3000W / 3000W	no	yes	yes	yes	yes	3000W / 3000W	yes	yes	yes	yes	yes
3500W / 3500W	no	yes	yes	no	no	3500W / 3500W	no	yes	yes	no	no
4000W / 4000W	no	yes	yes	yes	yes	4000W / 4000W	no	yes	yes	yes	yes
4500W / 4500W	no	yes	yes	yes	yes	4500W / 4500W	no	yes	yes	yes	yes
5000W / 5000W	no	yes	yes	yes	yes	5000W / 5000W	no	yes	yes	yes	yes
5500W / 5500W	no	no	yes	no	no	5500W / 5500W	no	yes	yes	no	no
6000W / 6000W	no	no	no	yes	yes	6000W / 6000W	no	yes	yes	yes	yes

Wattage	Recovery ▲ GPH Temperature Rise °F					Wattage	Recovery ▲ LPH Temperature Rise °C				
	60	80	90	100	120		34	45	50	56	67
1500W	10	8	7	6	5	1500W	38	30	26	23	19
2000W	14	10	9	8	7	2000W	53	38	34	30	26
2500W	17	13	11	10	9	2500W	64	49	42	38	34
3000W	21	15	14	12	10	3000W	79	57	53	45	38
3500W	24	18	16	14	12	3500W	91	68	61	53	45
4000W	28	21	18	16	14	4000W	106	79	68	61	53
4500W	31	23	21	19	15	4500W	117	87	79	72	57
5000W	34	26	23	21	17	5000W	129	98	87	79	64
5500W	38	29	25	23	19	5500W	144	110	95	87	72
6000W	41	31	28	25	21	6000W	155	117	106	95	79

▲ (GPH/LPH based on Non-Simultaneous operation, when Simultaneous operation the GPH/LPH will approximately double.)



### General:

All models ETL listed. These heaters are wired inter-locking (Non-Simultaneous, Single Phase) 240V with two 4500W elements, unless otherwise specified. All water and electrical connections are 3/4" NPT (19mm). All models certified at 300 PSI test pressure (2068 kPa) and 150 PSI working pressure (1034 kPa).

**Dimensions and specifications subject to change without notice in accordance with our policy of continuous product improvement.**



For field service, contact your professional installer or local Bradford White sales representative.

Sales / Technical Support 1-866-690-0961 / 905-203-0600

Fax 905-636-0666 / Email [bwccotech@bradfordwhite.com](mailto:bwccotech@bradfordwhite.com) / [www.bradfordwhite.com](http://www.bradfordwhite.com)

**Built to be the Best™**