

# Wellworth® Class Five® Toilet K-3575-RA

#### **Features**

- Vitreous china.
- Two-piece toilet.
- Regular height Elongated bowl.
- Class Five® flushing system.
- Includes right-hand polished chrome trip lever.
- 1.28 gpf (4.8 lpf).
- 2-1/8" (54 mm) fully glazed trapway.
- 12" (305 mm) rough-in.
- Less seat and supply.
- 11-1/4" (286 mm) x 8-1/4" (210 mm) water area.
- 30" (762 mm) x 19-5/8" (498 mm) x 28-1/4" (718 mm).
- Floor mount / Floor outlet.

## **Recommended Accessories**

K-4688 Toilet Seat K-7637 Angle Supply with Stop (single)

## Components

Product includes:

K-4198 Elongated Bowl K-4436-RA Toilet Tank

Additional included component/s: Tank cover, Trip lever, Bolt cap accessory pack, and Tank accessory pack.





## Codes/Standards

ASME A112.19.2/CSA B45.1 DOE - Energy Policy Act 1992 EPA WaterSense®

# **KOHLER® One-Year Limited Warranty**

See website for detailed warranty information.

### Available Color/Finishes

Color tiles intended for reference only.


Color	Code	Description
	0	White
	96	Biscuit
	47	Almond





# **Wellworth®**

Class Five® Toilet K-3575-RA



## **Technical Information**

All product dimensions are nominal.

Toilet type: Two-piece

Bowl shape: Elongated front

Flush type: Class Five

Trap passageway: 2-1/8" (54 mm)

Water Consumption

Full: 1.28 gpf (4.8 lpf)

Water surface size: 11-1/4" x 8-1/4" (286 mm x 210 mm)

Rim to water surface: 5-1/4" (133 mm) Rough-in: 12" (305 mm) Seat-mounting holes: 5-1/2" (140 mm)

#### **Notes**

Install this product according to the installation guide.

For back-to-back toilet installations: Use only a 45° double wye fitting.

