Sloar

OPTIONS Flow Rate

0.35 gpm (1 Lpm) (0.35GPM) 0.5 gpm (2 Lpm) (0.5GPM)

1.5 gpm (6 Lpm) (1.5GPM)

Spray Type

Multi-Laminar (MLM) Aerated (AER)

Finish

Polished Chrome (CP) Graphite (GR)

Mixer

Integrated Side Mixer (ISM) Mixer Not Included

Special Features

IQ Click (IQ) Carbon Offset (CO)

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.

Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.



Image for a standard EAF-350 shown

DESCRIPTION

Optima® Battery-Powered Deck-Mounted Mid Body Faucet

FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-Cast Metal Hand Washing Faucet with the following features:

- Double Infrared Sensor with Automatic Setting Feature and Microprocessor
- Bi-Stable Magnetic Solenoid Valve (for increased energy savings)
- Adjustable Hot Water Limit Set (with ISM Mixer)
- Water Supply Connection with Flexible High-Pressure Hose and Strainer
- 6V Lithium CR-P2 Commercial Battery included
- IR-Click feature permits activation of continuous run and temporary off modes
- Appropriate Mounting Hardware included
- 3 year limited warranty

DOWNLOADS

- EAF 350 Installation Instructions
- Faucet Spray Heads Repair and Maintenance Guide
- Optima Plus EAF 350 Repair and Maintenance Guide
- Additional Downloads

VIDEOS



PVD Special Finishes

Sloan 10500 Seymour Ave, Franklin Park, IL 60131 Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com