



WHERE QUALITY COMES FIRST


INTRODUCING the NEW Zilmet USA

ZEP-1 Stainless Steel Expansion Tank

and Shock Arrester for Tankless and POU Water Heaters with 2 gallons or less of total water volume

ZEP-1 was designed to provide maximum protection to the heat exchanger and the piping system on tankless water heaters, relieving problems associated with excess pressure by absorbing any potential increase in pressure within the unit or piping system; this helps prevent potentially costly leaks and repairs.





ZEP-1 can be installed below the isolation kit or anywhere on the cold water supply line between the heater and the check valve.

unique features:

- Tank has a 50 PSI factory precharge
- Air charge can be adjusted, and is serviceable
- Entire tank is constructed of 304 stainless steel
- 1/2" NPTM 304 stainless steel connection
- UV resistant and approved for outdoor installation
- Butyl membrane diaphragm
- NSF61 Certified

technical and dimensional data

| Model | Connection | 0 Diameter | H Height |
|-------|------------|------------|----------|
| | NPT | inches | inches |
| ZEP-1 | 1/2" | 3.5 | 4.6 |

| ight | |
|------|--|
| ies | |
| ò | |

North American Headquarters Zilmet USA

400 Frenchtown Road East Greenwich, RI 02818 401-884-4943 info@zilmetusa.com www.zilmetusa.com

Via del Santo, 242 - 35010 Limena (PD) - Italy Tel. +39 049 7664901 • Fax +39 049 767321 www.zilmet.it zilmet@zilmet.it

operating conditions

| maximum working pressure | 150 psi |
|-------------------------------|---------|
| maximum operating temperature | 140°F |

Production plants - Italy

Limena (PD) Via del Santo, 242 Via Visco, 2 • Via Colpi, 30 Via Tamburin, 15/17 Bagnoli di Sopra (PD) - Via V Strada, 21/23

Branches

Zilmet Deutschland GmbH www zilmet de Zilmet USA www.zilmetusa.com Zilmet UK www.zilmet.co.uk

