Extra portability and performance.

The Mini-Rooter XP gives you extra portability because 8" semi-pneumatic wheels let you keep the weight on the ground. An easy-grip handle folds down to save space and locks to use as an additional lifting handle. A roll bar protects the 1/3 hp motor when going up or down stairs. And the power cord and foot pedal can be stowed away on convenient cord wraps.

Mini-Rooter XP**

The XP gives you extra performance and value, enabling you to clear clogged drain lines from 1-1/4" to 4" in diameter with just one machine. The drum easily holds 75 feet of 3/8" or 1/2" cable and features a free floating inner drum with an integral distributor tube to help prevent cable tangling. By switching to the optional J-Drum or dual drum you can handle smaller drain lines.

You'll want to equip your XP with a power cable feed too. It makes a lot of tough jobs go much easier. Even with the power cable feed option, the drum is a snap to remove, taking less than a minute.

Of course the XP comes with an air foot pedal and ground fault circuit interrupter for safety, and General's patented Flexicore wire rope center cable for durability.



POWER CABLE FEED

A variable speed power cable feed attachment makes feeding and retrieving the cable much easier. It quickly adjusts between 3/8" and 1/2" cables without the need for tools or additional parts.

The toughest tools down the line.™





Mini-Rooter XP™



FLEXICORE® CABLE



Wire Rope Center Construction

Heavy-gauge wire coiled tightly around 42-strand aircrafttype wire rope and heat treated. Has unequalled strength and the right amount of flexibility. So tough it carries a oneyear warranty against defect or breakage.

Flexicore Patent Nos. 2,244,735 and 2,849,870

SPECIFICATIONS:

Weight:

67 lbs. (30 kg) with power cable feed and without cable.

Dimensions:

24" deep x 18" wide x 38" high with handle folded down. (61 cm x 46 cm x 96 cm)

Drum

Equipped with inner drum and distributor tube to prevent cable tangling under load. Quickly removable from frame.

Wheels:

8" semi-pneumatic tires with oilite bronze bushings.

Folding Handle:

Reduces storage space.

Cutter Set:

See below.

Motor:

1/3 hp with forward-off-reverse switch, spring loaded mounting for proper belt tension. Load speed 165 rpm.

Belt Guard:

High impact plastic secured with a tension knob and shock mounting.

Power Cable Feed:

(Optional) Drives 1/2" and 3/8" cables.

Foot Pedal:

Leaves operator's hands free to control cable. Uses air pressure, so there's no electrical contact between pedal and motor.

Power Cord:

10 ft. 3 wire. In-line ground fault circuit interrupter.

Leather Gloves:

With reinforced palm for hand protection.

J-Drum:


Capacity of 50 ft. of 1/4" or 5/16" Flexicore cable.

Dual Drum:

Capacity of 25 ft. of 1/4" or 5/16" in inner drum. 50 ft. of 5/16" or 3/8" Flexicore cable in outer drum.

Cutter Set





1-1/2 UC 1-1/2 U-Cutter

The toughest tools down the line.™

